

## **Brief Introduction**

ZKTeco developed ML100 and this smart lock is designed with a European Standard 5050 mortise and it is compatible with ZSmart APP.

ML100 can connect to Wi-Fi to unlock remotely, share passwords, trace records and manage lock users and visitors via smartphone. In addition, this smart lock offers multiple ways of unlocking including fingerprint, IC card and pass code.

As a result, ML100 is an ideal door lock management solution for apartments and private houses.

## **Features**



## Remote Mobile App. Supports

Unlock and manage the lock from anywhere



## **Audio Instructions**

User-friendly audio prompts, support English Spainish and Portuguese



### Capacitive Fingerprint Sensor

Fast verification for dry and rough fingers



#### Temporary Access

Share digital keys valid for specific time to friends or quests



#### NFC

Bind the IC card to your mobile wallet, and unlock your door with your smartphone or your IC card. No worries about misplacing your IC card



#### Wi-Fi Communication

Ensure a fast and stable by Wi-Fi IEEE 802.11b



## Random Passcode

Add random digits to protect your passcode from prying eyes



### **Emergency Charging Port**

Charging via the micro-USB port



#### Smart Alerts

Receive real-time notifications of low battery, hijack and offline



#### Lock Out Mode

All normal users (other than admin) will be locked out


## **Mobile Application**















## **Applicable Scenarios**







**Private Houses** 

**Apartments** 

Short-term Rental

# **Specifications**

Material	Housing (Aluminum Alloy)
Mortise	European Standard 5050 mortise
Keyless Authentication Methods	Smartphone, Fingerprint, Passcode, IC Card
Communication	Wi-Fi (IEEE 802.11b)
User Capacity	300
Fingerprint Capacity	100 (administrator: 10, normal user: 90)
Passcode Capacity	100 (administrator: 10, normal user: 90)
IC Card	100 (only normal user: 100)
Fingerprint Sensor	Capacitive Fingerprint Sensor
Power Supply	$4 \times AA$ Alkaline Battery (not included)
Battery Life	Up to 1 year
Backup Power Interface	Micro-USB
Door Thickness	35mm to 60mm
Dimensions (L*W*D)	265*60*22 (mm)
Operating Temperature	-25°C to 55°C
Operating Humidity	Up to 90% RH
Certification(s)	CE
Color Option(s)	Black
Supported Software/ Mobile App	ZSmart

# **Dimension(mm)**

