

SBTL6200

Dual Lane Swing Barrier with Modular Design



RFID



Fingerprint



QR code



Palm verification



Visible light facial recognition



SBTL6200 is a dual lane swing barrier designed and served as an additional lane besides SBTL6000 to meet specific client requirements. It is a swing barrier with a modular design that realizes fast switching between different readers. And reader installation can be completed by merely pull-out and plug-in. After installing the corresponding readers, SBTL6200 can support multiple verification methods, including RFID, fingerprint, QR code, palm verification and visible light facial recognition. Especially, palm verification and visible light facial recognition can realize touchless entrance control that avoids hands exposing to bacteria and boost public hygienic security.



Modular design readers are also suitable for FBL6000 Pro series.



Specifications

| | |
|--------------------------------|---------------------------------------|
| Power Requirements | AC 100 ~ 120V / 200 ~ 240V, 50 / 60Hz |
| Working Temperature | -28°C ~ 60°C |
| Working Humidity | 20% ~ 95% (non-condensing) |
| Working Environment | Indoor / Outdoor (if sheltered) |
| Lane Width (mm) | 635mm(optional≤850) |
| Infrared Sensor | 6 pairs |
| Dimension (L*W*H) | 1400 * 180 * 1000 (mm) |
| Dimension with Packing (L*W*H) | 1580 * 340 * 1270 (mm) |
| Weight with Packing (kg) | 85 |
| LED Indicator | Support |
| Cabinet Material | SUS304 Stainless Steel |
| Lid Material | SUS304 Stainless Steel + Acrylic |
| Barrier Material | Tempered Glass (optional: acrylic) |
| Barrier Movement | Swing |
| Emergency Mode | Support |
| MCBF | 2million |
| Warranty | 1 year |

Dimensions (mm)

