



DGLED-COB

0.7 | 0.9 | 1.2 | 1.5 | 1.8

Key Features

Excellent Display Effect



support 10000:1 high contrast
HDR10+ High dynamic display
120HZ Image refresh rate
DCI-P3 lever Wide color gamut coverage

Flexible Cabinet Design



standard boxeshalf-cabinet
45-degree cutting angles
maximum 90-degree right angle.

COB Technology



excellent reliability
superior pixel pitch

Flip Chip Technology



lowing temperature
improve image contrast
energy-saving

Applications



Security Command



Television Media



Broadcasting



Window Show

Specifications

Pixel Pitch	0.7	0.9	1.2	1.5	1.8
Using Environment	Indoor	Indoor	Indoor	Indoor	Indoor
Cabinet Size	600x337.5x42	600x337.5x43	600x337.5x44	600x337.5x45	600x337.5x46
Cabinet Weight (kg)	5.2	5.2	5.2	5.2	5.2
Cabinet Resolution	768x432	640x360	480x270	384x216	320x180
Ratio	16:09	16:09	16:09	16:09	16:09
Brightness	≤600	≤600	≤600	≤600	≤600
Refresh Rate	≤3,840	≤3,840	≤3,840	≤3,840	≤3,840
Color Temperature	2,500~10,000	2,500~10,000	2,500~10,000	2,500~10,000	2,500~10,000
Features	Common Cathode	Common Cathode	Common Cathode	Common Cathode	Common Cathode
Power Consumption (max)	≤420	≤420	≤420	≤420	≤420
Voltage	AC:100V~240V, 50-60Hz	AC:100V~240V, 50-60Hz	AC:100V~240V, 50-60Hz	AC:100V~240V, 50-60Hz	AC:100V~240V, 50-60Hz
Lifetime (Hrs)	100000	100000	100000	100000	100000
Operating Temperature	(-20)~ +60	(-20)~ +60	(-20)~ +60	(-20)~ +60	(-20)~ +60
Humidity Range	10 ~ 90	10 ~ 90	10 ~ 90	10 ~ 90	10 ~ 90